

Safety Data Sheet

Material: 60134151

**ELASTOSIL® E41
TRANSPARENT TF**

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Commercial product name: **ELASTOSIL® E41
TRANSPARENT TF**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:
Industrial.
adhesives .

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor: Wacker Chemie AG
Street/POB-No.: Gisela-Stein-Straße 1
State/postal code/city: D 81671 München
Telephone: +49 89 6279-0
Information about the Safety Data Sheet: Telephone +49 8677 83-4888
eMail WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information: Europe **+44 1235 239670**
Emergency Information: Africa and the Middle East **+44 1235 239671**
Emergency Information: Caribbean, Central America and South America except Chile and Colombia **+1 646 844 7309**
Emergency Information: Pakistan **+65 3158 1329**
Emergency Information: Bangladesh **+65 3158 1200**
Emergency Information: East Asia and Southeast Asia except Sri Lanka, Bangladesh and Pakistan **+65 3158 1074**
Emergency Information: Sri Lanka **+65 3158 1195**

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification	H-Code
Long-term (chronic) aquatic hazard, Category 3	H412
Serious eye damage/eye irritation, Category 2	H319
Skin corrosion/irritation, Category 2	H315
Flammable liquids, Category 2	H225

2.2 Label elements

Pictogram(s):



Signal Word: Danger

H-Code	Hazard Statements
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet

Material: 60134151

**ELASTOSIL® E41
TRANSPARENT TF**

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

P-Code	Precautionary Statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/ attention.

2.3 Other hazards

No data available.

Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Polydimethylsiloxane + auxiliary + silane + solvent

3.2.2 Hazardous ingredients

Type	CAS-No.	Substance	Content %
INHA	90622-56-3	C7 - C9 Isoalkanes	>=10 – <20
INHA	4253-34-3	Triacetoxymethylsilane	>=5 – <10
INHA	1067-33-0	Di-n-butyltin diacetate	>=0,025 – <0,1

Type: INHA: ingredient, VERU: impurity

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take persons to a safe place. Observe self-protection for first aid. Seek medical advice in the event of contact with this substance.

After contact with the eyes:

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice and clearly identify substance.

After contact with the skin:

Remove contaminated or soaked clothing. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice and clearly identify substance.

After inhalation:

Keep the patient calm. Protect against loss of body heat. Seek medical advice and clearly identify substance.

After swallowing:

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice and clearly identify substance.

Safety Data Sheet

Material: 60134151

ELASTOSIL® E41
TRANSPARENT TF

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media:**

alcohol-resistant foam , carbon dioxide , water mist , sprinkler system , sand , extinguishing powder .

Extinguishing media which must not be used for safety reasons:

water jet .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes.

5.3 Advice for firefighters**Special protective equipment for fire fighting:**

Use respiratory protection independent of recirculated air. Use tightly fitting chemical protection suit (see section 8). Keep unprotected persons away.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Secure the area. Wear personal protection equipment (see section 8). Task force: Use tightly fitting chemical protection suit (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Do not walk through spilled material. Ensure adequate ventilation. If material is released indicate risk of slipping.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods and material for containment and cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Precautions for safe handling:**

Ensure adequate ventilation. Must be syphoned off in situ. Keep away from incompatible substances in accordance with section 10. Observe information in section 8.

Precautions against fire and explosion:

Product may release acetic acid. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

Safety Data Sheet

Material: 60134151

**ELASTOSIL® E41
TRANSPARENT TF**

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

7.2 Conditions for safe storage, including any incompatibilities**Conditions for storage rooms and vessels:**

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

Minimum temperature allowed during storage and transportation: 0 °C**7.3 Specific end use(s)**

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

-

8.2 Exposure controls**8.2.1 Exposure in the work place limited and controlled****General protection and hygiene measures:**

Avoid exposure - obtain special instructions before use. Observe standard industrial hygiene practices for the handling of chemical substances. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Use with adequate ventilation. Preventive skin protection recommended. Remove contaminated, soaked clothing immediately. Clean work areas regularly. Provide emergency shower and eye-bath. Do not eat, drink or smoke when handling.

Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

Personal protection equipment:**Respiratory protection**

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Gas filter type ABEK (certain inorganic, organic and acidic gases and vapors; ammonia/amines), according to acknowledged standards such as EN 14387

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136.

Recommended Filter type: Combined filter type ABEK-P2 (certain inorganic, organic and acidic gases and vapors; ammonia/amines; particles), according to acknowledged standards such as EN 14387

For long or intense exposure, use respiratory protective equipment. Suitable respiratory equipment: Positive pressure self contained breathing apparatus, according to acknowledged standards such as EN 137.

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

tight fitting protective goggles, according to acknowledged standards such as EN 166.

Hand protection

Protective gloves are required at all times when handling the material, according to recognized standards such as EN374.

Recommended glove types: Protective gloves made of fluorinated rubber

thickness of the material: > 0,7 mm

Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of 5-layer laminate of PE and EVOH (4H)

thickness of the material: > 0,062 mm

Breakthrough time: > 480 min

Safety Data Sheet

Material: 60134151

ELASTOSIL® E41
TRANSPARENT TF

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

Skin protection

Chemical protective clothing, according to acknowledged standards such as EN 13034, full-body liquid-tight protection if necessary, according to acknowledged standards such as EN 14605, if handled uncovered. Please observe the instructions regarding permeability time which are provided by the supplier.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil. Normally neutralisation is required before waste water is introduced into purification plants. Do not introduce large amounts into purification plants.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Property:	Value:	Method:
Appearance		
Physical state	liquid	
Form	paste	
Colour	colourless	
Odour		
Odour	similar to acetic acid	
Odour limit		
Odour limit	no data available	
pH-Value		
pH-Value	Not applicable. Insoluble in water.	
Melting point/freezing point		
Melting point / melting range	exempt	
Initial boiling point and boiling range		
Boiling point / boiling range	111 °C at 1013 hPa	(not specified)
Flash point		
Flash point	14 °C	(ISO 3679)
Sustained combustibility	not determined	
Evaporation rate		
Evaporation rate	no data available	
Upper/lower flammability or explosive limits		
Lower explosion limit	1,2 Vol-%	(not specified)
Upper explosion limit	7 Vol-%	(not specified)
Vapour pressure		
Vapour pressure	29 hPa at 20 °C	(not determined)
Solubility(ies)		
Water solubility	practically insoluble	
Vapour density		
Relative gas/vapour density	no data available	
Relative Density		
Relative Density	1,048 (23 °C)	(DIN EN ISO 2811-2)
	(Water / 4 °C = 1,00)	
Density	1,048 g/cm ³ (23 °C)	(DIN EN ISO 2811-2)
Partition coefficient: n-octanol/water		
Partition coefficient: n-octanol/water	not applicable	
Auto-ignition temperature		
Ignition temperature	412 °C	(DIN EN ISO/IEC 80079-20-1)
Decomposition temperature		
Thermal decomposition	exempt	
Viscosity		
Viscosity, dynamic	65000 mPa.s at 23 °C	(Brookfield)

Safety Data Sheet

Material: 60134151

ELASTOSIL® E41
TRANSPARENT TF

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

Viscosity, kinematic: not applicable

Molecular mass

Molecular mass: not applicable

9.2 Other information

Hydrolysis products reduce the flash point. Explosion limits for released acetic acid: 4 - 17%(V).

SECTION 10: Stability and reactivity**10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known. Violent reactions are possible with various chemicals.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

Moisture, heat, open flames, and other sources of ignition.

10.5 Incompatible materials

Reacts with: water, basic substances and alcohols. The reaction takes place with the formation of acetic acid.

10.6 Hazardous decomposition products

Acetic acid by hydrolysis. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****11.1.1 General information**

Data derived for the product as a whole are of higher priority than data for single ingredients.

11.1.2 Acute toxicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

Acute toxicity estimate (ATE):ATE_{mix} (Oral): > 2000 mg/kg**Data on substances:****C7 - C9 Isoalkanes:**

Exposure routes	Result/Effect
Oral	LD50 > 5000 mg/kg Species: Rat, Source: ECHA
dermal	LD50 > 2000 mg/kg Species: Rabbit, Source: literature
by inhalation (vapour)	LC50 > 21 mg/l; 4 h Mortality has been observed at the given dose level. Species: Rat, Source: ECHA

11.1.3 Skin corrosion/irritation**Product details:**

irritating

The given result is based on an evaluation of the whole database for this endpoint ("weight of evidence").

(Species: Rabbit, Source: Conclusion by analogy)

Data on substances:

Safety Data Sheet

Material: 60134151

**ELASTOSIL® E41
TRANSPARENT TF**

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

C7 - C9 Isoalkanes:

irritating
(Species: not specified, Source: ECHA)

11.1.4 Serious eye damage/eye irritation**Product details:**

irritating
The given result is based on an evaluation of the whole database for this endpoint ("weight of evidence").
(Species: Rabbit, Source: Conclusion by analogy)

Data on substances:**C7 - C9 Isoalkanes:**

No eye irritation
(Species: Rabbit, Source: ECHA)

11.1.5 Respiratory or skin sensitization**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

Data on substances:**C7 - C9 Isoalkanes:**

Exposure routes	Result
Skin contact	Does not cause skin sensitization. (Species: Guinea pig, Test system: Maximisation Test, Test substance: read-across substance, Source: ECHA)

11.1.6 Germ cell mutagenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Carcinogenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Reproductive toxicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity - single exposure**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

Data on substances:**C7 - C9 Isoalkanes:**

Vapours may be narcotising.

11.1.10 Specific target organ toxicity - repeated exposure**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.11 Aspiration hazard**Assessment:**

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

Safety Data Sheet

Material: 60134151

ELASTOSIL® E41
TRANSPARENT TF

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

Data on substances:**C7 - C9 Isoalkanes:**

Product can pose an aspiration hazard.

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

11.2.2 Further toxicological information

In contact with dampness product separates a small quantity of acetic acid (64-19-7) which irritates skin and mucous membranes.

SECTION 12: Ecological information**12.1 Toxicity****Assessment:**

For the product as a whole, no test data is available.

12.2 Persistence and degradability**Assessment:**

Polymer component: biologically not degradable. Elimination by adsorption to activated sludge.

12.3 Bioaccumulative potential**Assessment:**

Polymer component: No adverse effects expected.

12.4 Mobility in soil**Assessment:**

Polymer component: insoluble in water.

12.5 Results of PBT and vPvB assessment

PBT assessment

No data available.

vPvB Assessment

No data available.

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

none known

SECTION 13: Disposal considerations**13.1 Waste treatment methods****13.1.1 Material****Recommendation:**

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

Safety Data Sheet

Material: 60134151

**ELASTOSIL® E41
TRANSPARENT TF**

Version 1.4 (GHS_INT)

Print Date 29.10.2026

Date of last alteration: 04.04.2026

13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used.
Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR: UN1993
RID: UN1993
IMDG: UN1993
ICAO/IATA: UN1993

14.2 Proper shipping name

ADR: Entzündbarer flüssiger Stoff, n.a.g. (C7 - C9 Isoalkane, n-Propanol)
ADR (Domestic transport regulations).....: Flammable liquid, n.o.s (C7 - C9 Isoalkanes, n-Propanol)
RID: Entzündbarer flüssiger Stoff, n.a.g. (C7 - C9 Isoalkane, n-Propanol)
RID (Domestic transport regulations): Flammable liquid, n.o.s (C7 - C9 Isoalkanes, n-Propanol)
IMDG: Flammable liquid, n.o.s. (C7 - C9 Isoalkanes, n-Propanol)
ICAO/IATA: Flammable liquid, n.o.s. (C7 - C9 Isoalkanes, n-Propanol)

14.3 Transport hazard class

ADR: 3
(Limited quantity (LQ): 1L)
RID: 3
IMDG: 3
ICAO/IATA: 3

14.4 Packing group

ADR: II
RID: II
IMDG: II
ICAO/IATA: II

14.5 Environmental hazards

Environmentally hazardous: no
Marine pollutant (IMDG): no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Maritime transport in bulk according to IMO instruments

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

15.2 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan: **ENCS** (Handbook of Existing and New Chemical Substances):
This product is listed in, or complies with, the substance inventory.
Australia: **AIIC** (Australian Inventory of Industrial Chemicals):
This product is listed in, or complies with, the substance inventory.
China.....: **IECSC** (Inventory of Existing Chemical Substances in China):
This product is listed in, or complies with, the substance inventory.

Safety Data Sheet

Material: 60134151
ELASTOSIL® E41
TRANSPARENT TF

Version 1.4 (GHS_INT)
Print Date 29.10.2026
Date of last alteration: 04.04.2026

- Canada :
Philippines..... :
United States of America (USA)..... :
Taiwan :
European Economic Area (EEA)..... :
South Korea (Republic of Korea) :
- DSL** (Domestic Substance List):
This product is listed in, or complies with, the substance inventory.
PICCS (Philippine Inventory of Chemicals and Chemical Substances):
This product is listed in, or complies with, the substance inventory.
TSCA (Toxic Substance Control Act Chemical Substance Inventory):
All components of this product are listed as active or are in compliance with the substance inventory.
TCSI (Taiwan Chemical Substance Inventory):
This product is listed in, or complies with, the substance inventory. General note:
The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
REACH (Regulation (EC) No 1907/2006):
General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"):
Please approach your regular contact for more detailed information.

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Classification	Rationale:
Long-term (chronic) aquatic hazard, Category 3	Calculation method
Serious eye damage/eye irritation, Category 2	On basis of test data.
Skin corrosion/irritation, Category 2	On basis of test data.
Flammable liquids, Category 2	On basis of test data.

- End of Safety Data Sheet -