

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

**1. Product and company identification****1.1 Identification of the substance or preparation:**

**Trade name** WACKER® CATALYST T 12  
Product group: R&D Material  
Use of the Substance/Mixture Industrial, Commercial.  
Intermediate chemical

**1.2 Company/undertaking identification:**

Manufacturer/distributor: Wacker Chemie AG  
Gisela-Stein-Straße 1  
81671 München  
Germany

Customer information: Wacker Chemical Corporation  
4950 S State Road  
Ann Arbor, MI 48108  
InfoLine:  
Tel (517) 264-8240  
Hours of operation:  
Monday - Friday, 8 am to 5 pm (eastern standard time)  
Corporate website: www.wacker.com

Emergency telephone no. (24h): **(517) 264-8500**

Transportation emergency: (800) 424-9300 (CHEMTREC, USA)  
(703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

**2. Hazards identification****2.1 Classification of the substance or mixture****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200):**Hazards for the product as supplied

| Classification  | H-Code |
|---|--------|
| Flammable liquids, Category 3   | H226   |
| Specific target organ toxicity - repeated exposure, Category 1 (thymus) | H372   |
| Reproductive toxicity, Category 2                                       | H361d  |

**2.2 Label elements****GHS-Labeling:**

Pictogram(s):



Signal word: Danger

| H-Code | Hazard statements  |
|--------|--|
| H226   | Flammable liquid and vapour.   |
| H361d  | Suspected of damaging the unborn child.                                  |
| H372   | Causes damage to organs (thymus) through prolonged or repeated exposure. |

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

| P-Code | Precautionary statements   |
|--------|--|
| P201   | Obtain special instructions before use.  |
| P210   | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233   | Keep container tightly closed.   |
| P243   | Take action to prevent static discharges.  |
| P260   | Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  |
| P280   | Wear protective gloves/protective clothing/eye protection.                                     |
| P314   | Get medical advice/ attention if you feel unwell.  |
| P405   | Store locked up.   |

The following percentage of the mixture consists of ingredient(s) with unknown acute inhalation toxicity: 7.4 %.

The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 7.4 %.

**2.3 Other hazards**

No data available.

Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**3. Composition/information on ingredients****3.1 Chemical characterization (preparation)**

Chemical characterization

Organotin compound+Silicic acid ester+Polydimethylsiloxane

**3.2 Information on ingredients:**

| Type | Numerical identifier  | Substance   | Content [wt. %] | Note |
|------|-----------------------|---|-----------------|------|
| INHA | 682-01-9<br>CAS-No.   | Tetrapropyl orthosilicate   | >=40 – <50      |      |
| INHA | 93925-43-0<br>CAS-No. | Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)diethylstannane | >=5 – <10       | R    |
| INHA | 68299-15-0<br>CAS-No. | Bis(neodecanoyloxy)diethylstannane  | >=1 – <5        |      |

**Type:** INHA - ingredient, VERU - impurity. \*\*\* **Note:** C1 - IARC carcinogen, C2 - NTP carcinogen, C3 - OSHA carcinogen, R - reproductive toxin.

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

**4. First-aid measures****4.1 General information:**

Get medical attention immediately. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

**4.2 If inhaled**

If inhaled remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen.

**4.3 In case of skin contact**

For skin contact, immediately wipe away excess material. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

**4.4 In case of eye contact**

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

**4.5 If swallowed**

Induce drinking plenty of water in small portions. If swallowed, do not induce vomiting. Give activated charcoal in a premixed suspension, if available. If vomiting does occur, give additional fluids. Get medical attention. Designate the product. Show label if possible.

**5. Fire-fighting measures****5.1 Flammable properties:**

| Property:                                  | Value:                      | Method:     |
|--|-----------------------------|-------------|
| Flash point.....                           | 53 °C (127 °F)              | (DIN 53213) |
| Sustained combustibility.....              | 80 °C (176 °F)              | (ISO 9038)  |
| Boiling point/boiling range .....          | 175 °C (347 °F) at 1013 hPa |             |
| Lower explosion limit.....                 | not determined              |             |
| Upper explosion limit.....                 | not determined              |             |
| Ignition temperature .....                 | 255 °C (491 °F)             | (DIN 51794) |
| NFPA Hazard Class (comb./flam.liquid)..... | II                          |             |

**5.2 Fire and explosion hazards:**

Caution! OSHA Combustible liquid and vapor. This material will flash but does not sustain combustion.

**5.3 Recommended extinguishing media:**

water-spray , carbon dioxide , dry chemical , dry sand or alcohol-resistant foam .

**5.4 Unsuitable extinguishing media:**

sharp water jet .

**5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases**

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide , tin dioxide and incompletely burnt hydrocarbons .

**5.6 Fire fighting procedures:**

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Use respiratory protection independent of recirculated air. Cool endangered containers with water.

**6. Accidental release measures****6.1 Precautions:**

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

**HAZWOPER PPE Level: C**

**6.2 Containment:**

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

**6.3 Methods for cleaning up**

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

**6.4 Further information:**

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

**7. Handling and storage****7.1 General information:**

Avoid exposure by technical measures or personal protective equipment.

**7.2 Handling****Precautions for safe handling:**

Ensure adequate ventilation. Must be syphoned off in situ. Spilled substance increases risk of slipping. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Observe information in section 8. Keep away from incompatible substances in accordance with section 10.

**Precautions against fire and explosion:**

Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

**7.3 Storage****Conditions for storage rooms and vessels:**

Observe local/state/federal regulations.

**Advice for storage of incompatible materials:**

Observe local/state/federal regulations.

**Further information for storage:**

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

**8. Exposure controls and personal protection****8.1 Engineering controls****Ventilation:**

Use only with adequate ventilation.

**Local exhaust:**

To control flammable/combustible vapors: Local exhaust ventilation which meets the requirements of ANSI Z9.2 is recommended to control airborne contaminants at the point of use.

**8.2 Associate substances with specific control parameters such as limit values****Maximum airborne concentrations at the workplace:**

| Substance               | Type      | mg/m <sup>3</sup> | ppm | Dust fract. |
|-------------------------|-----------|-------------------|-----|-------------|
| Tin compounds (organic) | OSHA PEL  | 0.1               |     |             |
| Tin compounds (organic) | ACGIH TWA | 0.1               |     |             |

Re Tin compounds (organic): STEL is 0,2 mg/m<sup>3</sup>, skin notation (ACGIH).

**8.3 Personal protection equipment (PPE)****Respiratory protection:**

Recommendation in case of long or strong exposure: A NIOSH approved air purifying respirator equipped with universal multi-contaminant multi-gas/vapor cartridges is recommended if overexposure to chemical vapors could occur. If eye-irritating dusts or vapors are present, a full-face respirator should be worn.

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

**Hand protection:**

butyl rubber protective gloves . At any sign of decay or chemical permeability remove gloves immediately and replace.

**Eye protection:**

Safety glasses with side shields or chemical safety goggles.

**Other protective clothing or equipment:**

Additional skin protection, such as SARANEX coated Tyvek apron, over-sleeves, lab coat, coveralls, or protective suit should be worn if splashing could occur. Provide eye bath and safety shower.

**8.4 General hygiene and protection measures:**

Avoid contact with eyes, skin and clothing. Avoid breathing dust/vapor/mist/gas/aerosol. When handling do not eat, drink, smoke or apply cosmetics. Wash thoroughly after handling.

**9. Physical and chemical properties****9.1 Information on basic physical and chemical properties**

| Property:                                    | Value:                              | Method:     |
|--|-------------------------------------|-------------|
| Physical state .....                         | liquid                              |             |
| Colour .....                                 | colourless                          |             |
| Odour .....                                  | faint                               |             |
| Odour Threshold .....                        | no data available                   |             |
| Melting point.....                           | not determined                      |             |
| Boiling point/boiling range .....            | 175 °C at 1013 hPa                  |             |
| Lower explosion limit.....                   | not determined                      |             |
| Upper explosion limit.....                   | not determined                      |             |
| Flash point.....                             | 53 °C                               | (DIN 53213) |
| Ignition temperature .....                   | 255 °C                              | (DIN 51794) |
| Thermal decomposition.....                   | exempt                              |             |
| pH .....                                     | Not applicable. Insoluble in water. |             |
| Viscosity, kinematic.....                    | no data available                   |             |
| Viscosity, dynamic.....                      | 15 mPa.s at 23 °C                   |             |
| Water solubility.....                        | practically insoluble               |             |
| Partition coefficient: n-octanol/water ..... | not applicable                      |             |
| Vapour pressure.....                         | 15 hPa at 20 °C                     |             |
| Density .....                                | 0.96 g/cm <sup>3</sup> (20 °C)      | (DIN 51757) |
| Relative vapour density .....                | no data available                   |             |
| Particle Size Distribution .....             | Not applicable.                     |             |

**9.2 Other information**

Hydrolysis products reduce the flash point.

| Property:                     | Value:            | Method:    |
|-------------------------------|-------------------|------------|
| Sustained combustibility..... | 80 °C             | (ISO 9038) |
| Evaporation rate.....         | no data available |            |
| Molecular weight .....        | not applicable    |            |

**10. Stability and reactivity****10.1 General information:**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

**10.2 Conditions to avoid**

Moisture, heat, open flames, and other sources of ignition.

**10.3 Materials to avoid**

Reacts with water, basic substances and acids. The reaction takes place with the formation of alcohols.

**10.4 Hazardous decomposition products**

Alcohols by hydrolysis. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

**10.5 Further information:**

Hazardous polymerization cannot occur.

**11. Toxicological information****11.1 Information on toxicological effects****11.1.1 Acute toxicity****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Acute toxicity estimate (ATE):**ATE<sub>mix</sub> (by inhalation / dust/mist): > 5 mg/l/4 hATE<sub>mix</sub> (Oral): > 2000 mg/kg**11.1.2 Skin corrosion/irritation****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.3 Serious eye damage/eye irritation****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.4 Respiratory or skin sensitization****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.5 Germ cell mutagenicity****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.6 Carcinogenicity****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.7 Reproductive toxicity****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.8 Specific target organ toxicity - single exposure****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.9 Specific target organ toxicity - repeated exposure****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.10 Aspiration hazard****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.11 Endocrine disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

**11.1.12 Further toxicological information**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other information: According to literature iso-propanol (67-63-0) is irritating to mucous membranes, slightly irritating to the skin, causes degreasing of the skin and is narcotic.

**12. Ecological information****12.1 Toxicity****Assessment:**

For the product as a whole, no test data is available.

**12.2 Persistence and degradability****Assessment:**

Polymer component: biologically not degradable. Elimination by adsorption to activated sludge.

**12.3 Bioaccumulative potential****Assessment:**

Polymer component: No adverse effects expected.

**12.4 Mobility in soil****Assessment:**

Polymer component: insoluble in water.

**12.5 Results of PBT and vPvB assessment**

PBT assessment

No data available.

vPvB Assessment

No data available.

**12.6 Endocrine disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7 Other adverse effects**

none known

**13. Disposal considerations****13.1 RCRA Waste Classification:**

D001 (Ignitable)

This classification applies only to the material as it was originally produced.

**13.2 Product disposal**

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

**13.3 Packaging disposal**

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

**14. Transport information****14.1 US DOT & CANADA TDG SURFACE**

Valuation .....: Not regulated for transport  
 Other Information .....: This material has been tested and does not sustain combustion. DOT Class 3 labels and placards are not required.

**14.2 Transport by sea IMDG-Code**

Valuation .....: Not regulated for transport  
 Comment.....: Not regulated in Class 3 - IMDG 2.3.1.3 - as the substance does not sustain combustion!

**14.3 Air transport ICAO-TI/IATA-DGR**

Valuation .....: Not regulated for transport  
 Comment.....: Not regulated in Class 3 - IATA 3.3.1.3 / ICAO 3.1.3 - Substance does not sustain combustion!  
 Due to safety reasons no air transport in totes (IBC) or vented packaging!

**15. Regulatory information****15.1 U.S. Federal regulations****TSCA inventory status and TSCA information:**

This material or its component(s) is in compliance with TSCA under a Low Volume Exemption.

**TSCA 12(b) Export Notification:**

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

**CERCLA Regulated Chemicals:**

This material does not contain any CERCLA regulated chemicals.

**SARA 302 EHS Chemicals:**

This material does not contain any SARA extremely hazardous substances.

**SARA 311/312 Hazard Class:**

Reproductive toxicity. Specific target organ toxicity (single or repeated exposure). Flammable (gases, aerosols, liquids, or solids)

**SARA 313 Chemicals:**

This material does not contain any SARA 313 chemicals above de minimus levels.

**HAPS (Hazardous Air Pollutants):**

| CAS-No.  | Chemical      | Upper limit |
|----------|---------------|-------------|
| 141-78-6 | Ethyl acetate | <=0.0450 %  |

**15.2 US State Regulations****US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)**

This material does not contain any chemicals known to the State of California to cause cancer.

This material does not contain any chemicals known to the State of California to cause reproductive effects.

**Massachusetts Right To Know**

Product does not contain any listed chemicals

**15.3 Details of international registration status**

Relevant information about individual substance inventories, where available, is given below.

Japan .....: **ENCS** (Handbook of Existing and New Chemical Substances):  
 This product is listed in, or complies with, the substance inventory.  
 Australia .....: **AIIC** (Australian Inventory of Industrial Chemicals):  
 This product is listed in, or complies with, the substance inventory.  
 China.....: **IECSC** (Inventory of Existing Chemical Substances in China):  
 This product is listed in, or complies with, the substance inventory.

**SAFETY DATA SHEET**

Material: 60006302

WACKER® CATALYST T 12

Version 2.7 (US)

Print Date 06/12/2026

Date of last alteration: 04/04/2026

|                                       |   |
|---------------------------------------|---|
| Canada .....                          | : <b>DSL</b> (Domestic Substance List):<br>This product is not listed or in compliance with the substance inventory.  |
| Philippines.....                      | : <b>PICCS</b> (Philippine Inventory of Chemicals and Chemical Substances):<br>This product is not listed or in compliance with the substance inventory.  |
| Taiwan .....                          | : <b>TCSI</b> (Taiwan Chemical Substance Inventory):<br>This product is listed in, or complies with, the substance inventory. General note:<br>The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed<br>or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan<br>exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each<br>ingredient). It is the duty of the importing/manufacturing legal entity to take care of<br>this obligation. |
| European Economic Area (EEA).....     | : <b>REACH</b> (Regulation (EC) No 1907/2006):<br>General note: the registration obligations for substances imported into the EEA or<br>manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by<br>the said supplier. The registration obligations for substances imported into the EEA<br>by customers or other downstream users must be fulfilled by the latter.  |
| South Korea (Republic of Korea) ..... | : <b>AREC</b> (Act on Registration and Evaluation of Chemicals; "K-REACH"):<br>Please approach your regular contact for more detailed information.  |

**16. Other information****16.1 Additional information:**

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on [www.wacker.com](http://www.wacker.com). WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

**16.2 Glossary of Terms:**

|   |   |
|---|---|
| ACGIH - American Conference of Governmental Industrial Hygienists | ppm - Parts per Million                             |
| DOT - Department of Transportation                                | SARA - Superfund Amendments and Reauthorization Act |
| hPa - Hectopascals  | STEL - Short Term Exposure Limit                    |
| mPa*s - Milli Pascal-Seconds                                      | TSCA - Toxic Substances Control Act                 |
| OSHA - Occupational Safety and Health Administration              | TWA - Time Weighted Average                         |
| PEL - Permissible Exposure Limit                                  |   |

| Flash point determination methods ..... | Common name                   |
|---|-------------------------------|
| ASTM D56.....                           | Tagliabue (Tag) closed cup    |
| ASTM D92, DIN 51376, ISO 2592 .....     | Cleveland open cup            |
| ASTM D93, DIN 51758, ISO 2719 .....     | Pensky-Martens closed cup     |
| ASTM D3278, DIN 55680, ISO 3679 .....   | Setaflash or Rapid closed cup |
| DIN 51755.....                          | Abel-Pensky closed cup        |

**16.3 Conversion table:**

Pressure:.....: 1 hPa \* 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa  
Viscosity:.....: 1 mPa\*s = 1 centipoise (cP)