**REMET UK Limited**

Unit 44, Riverside 2,
Sir Thomas Longley Road,
Rochester, Kent ME2 4DP
Tel: +44 (0) 1634 226240
Fax: +44 (0) 1634 226241
www.remet.com

**Technical Information Sheet**

# Utility B75

Utility B75 is a soft patching wax for pattern repair. It can be smeared onto damaged patterns using the fingers or can be brushed on in the molten state. It is compatible with other products in Remet UK's range.

## IMPORTANT

Avoid overheating the wax (100°C max) or holding it at elevated temperatures for long periods. Doing so will thermally degrade the product. Avoid skin contact with the molten material and avoid inhaling fumes from it. See the relevant Material Safety Data Sheet for more information.

## TYPICAL PROPERTIES

| | | |
|---|---|---|
| Melting Point (°C) | (IP.371) | 75 |
| Congealing Point (°C) | (IP.76) | 69 |
| Penetration @ 25°C (dmm) | (ASTM.D1321) | 70 |
| Viscosity @ 99 °C (cSt) | (IP.71) | 12 |
| Ash Content (%, w/w) | (DCF.2) | 0.030 Max. |
| Colour | (DCF.4) | Natural / Green |



Registered Name: Remet UK Limited
Registered Office: 44 Riverside II, Sir Thomas Longley Road, Rochester, Kent. ME2 4DP
Registered No: 4780567 England